

## **SOLAR MPPT CHARGE CONTROLLOR-240V**

Technical Spe		al al	2408/1/	10 A
	Model  Technology		240V/40A MPPT	
Input (Solar)	recimology			
	Max PV Input Voltage		440.00V	
	Max PV Input Current		40.0A	
	Max PV Array Power (Wp)		10000W	
	Nominal Battery Voltage		240.00V DC	
	Bulk Voltage		288.00 V (Adjustable 284.00 -288.00 Volts)	
	Float Voltage		276.00 V (Adjustable 272.00 -276.00 Volts)	
Protections	Output Over Voltage		Provided	
	Battery over charge		Provided	
	PV Reverse		Provided	
	Battery Reverse		Provided	
	Reverse Current Flow From Battery to Panel		Provided	
Indications	LED	Main function	LED Status	Sub Function
	GREEN	Charging mode	Blinking with 1 Second 1 interval	Solar Power Nil
			Blinking with 1 Second 2 interval	Solar Charger ON
			Blinking with long on time	Solar Charger OFF
	ORANGE	Orange LED: Fault mode	Orange LED continuous on.	Reverse polarity of PV
	RED	Red LED: Fault mode	Red LED continuous on.	Reverse polarity of Battery
Overall	Temperature		0-50°C	
	Relative Humidity		0-95% Non Condensing	
	Dimensions (W×D×H) are in mm		500×250×140	
	Weight		18 kgs	